



Driving Technology



The 8525 G2 is a Windows CE 5.0 based vehicle-mount computer engineered to deliver Flexibility, Integration, Ruggedness and Ergonomics (FIRE) required for mobile data collection in the harshest mobile environments. The 8525 G2 can also be configured to operate in Intense and Cold Environments (ICE). The features of Fire and Ice put the 8525 G2 in a class by itself. The 8525 G2 offers maximum performance with robust expansion and connectivity options. It is easy to see why the 8525 G2 is the only choice for use in the harshest and most demanding environments like warehouses, freezers, ports, yards and other local-area mobile applications. And, like the rest of Psion Teklogix' mobile computing products, the 8525 G2 is based on industry standards to ensure it integrates easily with your existing or future infrastructure.



ADVANTAGES

- **Wide range power supply:** 10 - 90 volts means no need for an external pre-regulator and reduced cost.
- **Internal back-up battery:** No need for an external UPS back up power supply, and no worry about lost data.
- **Freezer condensing options:** The 8525 G2 is available in a freezer-rated version that included heated components rated for temperatures as low as -22°F (-30°C).
- **Bold, bright, crisp, color:** Transmissive display allows the screen to be seen clearly even in bright lighting conditions.
- **Enhanced connectivity:** Multiple expansion ports including RS232 (DB9), USB device and several USB hosts. These ports are ideal to connect multiple peripherals like undecoded or decoded bar code scanners, hand-held imagers and printers.
- **Radio options:** 802.11b/g, Bluetooth and Narrowband radio options in the same terminal gives you maximum flexibility for wireless connectivity.
- **Magnesium housing:** 30% lighter than aluminum, has a greater strength to weight ratio than aluminum or steel.



8525 G2 Vehicle-Mount Computer



Specifications



PROCESSOR & MEMORY

- Intel XScale PXA 270 @ 520MHz
- On-board RAM: 128 MByte SDRAM
- On-board ROM: 64 MByte FLASH

OPERATING SYSTEMS

- Windows CE 5.0

PROGRAMMING ENVIRONMENT

- HTML, XML
- Java Virtual Machine
- SDK supporting Microsoft Visual Studio

WIRELESS COMMUNICATIONS

- RA2040 Radio – 802.11b/g Compact Flash Baud rate, power output
 - 802.11b, 1, 2, 5.5, 11 Mbps, 32mW
 - 802.11g, 6, 9, 12, 18, 24, 36, 48, 54 Mbps, 20mW

Security

- WPA 1, 801.11i/WPA 2
- Encryption – Dynamic WEP, AES
- EAP Types - LEAP, PEAP MS-CHAP v2, PEAP GTC, EAP-FAST, TLS, TTLS.
- Narrowband 400-500MHz radio
- Integrated Bluetooth radio
- External antenna options

APPLICATION SOFTWARE

- Internet Explorer
- Open TekTerm
- Terminal Emulations:
 - TESS
 - ANSI
 - IBM 3270, IBM 5150
 - HP 23 GL
 - HTML

USER INTERFACE

- Colour Display
 - 8525: 1/2 VGA 640x240 (8.8")
 - Transmissive TFT industrial for both indoor/sunlight readability
 - CCFL Backlight, 220 cd/m² with brightness control.
- Touchscreen
 - Passive stylus or finger operation
 - Rugged 5-wire technology
 - Enhanced anti-glare coating
- Keyboard Options
 - On-screen keyboard
 - 3 Hardware keyboard formats available
 - ABC (10 F-keys)
 - QWERTY (10 F-keys)
 - AZERTY (10 F-keys)
 - 68 key PC like format

- EL backlight
- Ergonomic
- Dedicated function keys
- Epoxy coated elastomeric

- Indicators & Controls
 - Internal 95 dBA beeper w/ volume control
 - 4 indicators RX/TX, API, SCAN, PWR/CHG
 - Power indicator on radio dome

INTERNAL EXPANSION SLOTS

- One SD I/O (MultiMediaCard) slot
- One Type II Compact Flash
- Two Type III/one Type III PCMCIA slot
- Convenient access to slots via sealed end cap

EXTERNAL PORTS

- One tether port with:
 - One RS232 serial port (decoded scanner; printer)
 - Undecoded scanner port
 - USB host port
- One port with:
 - DB9 plug RS232 (optional 5/12V on pin 9)
- One high density port with:
 - 1 RS232 serial communication port
 - 1 USB device port
 - 2 USB host ports

SIZE AND WEIGHT

- Size: 11 3/4" W x 4 5/8" H x 11 1/2" L (29.84 cm W x 11.75 cm D x 29.21 cm L)
- Weight: approximately 9.5 lbs (4.086 kg)
- Includes integrated UPS, standard radio

ENVIRONMENTAL

- Standard:
 - Operating temp: -4°F to 140°F (-20°C to 60°C)
 - Storage temp: -31°F to 140°F (-35°C to +70°C)
 - Humidity: 5 - 95% RH non-condensing
- Freezer:
 - Operating temp: -22°F to 140°F (-30°C to +60°C)
 - Storage temp: -31°F to 140°F (-35°C to +70°C)
 - Humidity: 5 - 95% RH condensing with internal heating
- Rain/Dust: IEC 529, classification IP66
- 3 axis Vibration: 1.5 g RMS PSD (4 – 500 Hz)
- 3 axis Shock 30 g 11 ms saw tooth

POWER MANAGEMENT

- Internal power supply 10-90VDC designed for forklift power
- Internal UPS (12.6V Li-Ion backup battery) for full terminal operation during power loss / brown out
- Built-in fast charger
- > 1 week real-time clock backup

NETWORK MANAGEMENT

- SNMP MIB 2 support
- MapRF
- Mobile Control Center (MCC)
- Wavelink Avalanche
- Remote WLAN management

ACCESSORIES

- Multiple mounting options

APPROVALS:

- Safety: UL 60950 3rd Ed, CSA 60950-00, LVD EN 60950-1:2001
 - EMC: FCC Part 15 Class B
 - Complies with European R & TTE Directive
- * Note this product will carry the CE Mark.



Product is RoHS compliant

* Specifications subject to change without notice.